

PRO-SPRAY®

Professional-Grade Sprinkler Bodies

Hunter®



RUGGED AND BUILT TO LAST

Built to thrive in the most rugged irrigation trenches, Hunter Pro-Spray Sprinkler Bodies are precision engineered to ensure long-lasting, reliable performance in residential and commercial applications.

Available in heights from shrub to 30 cm, Pro-Spray Sprinkler Bodies feature durable construction for long field life. The exclusive body cap design prevents leaks even when loosened, and the two-piece ratchet is reliable and easy to adjust.

Pro-Spray Sprinkler Bodies are compatible with Pro High-Efficiency, Pro Adjustable, Pro Fixed, and MP Rotator® Nozzles..

All models also include a user-friendly, pull-ring flush cap to keep debris and clogging to a minimum. In addition, Pro-Spray Sprinkler Bodies work with all industry standard female nozzles, offering maximum flexibility.



Shown here: PRS40 shrub, Pro-Spray 5 cm, PRS30 and PRS40 10 cm, Pro-Spray 15 cm, and PRS30 and PRS40 30 cm sprays



The Pro-Spray line incorporates a heavy-duty, ribbed body and durable cap engineered to withstand the harshest environments.

CO-MOULDED WIPER SEAL

This pressure-activated, multi-function wiper seal was designed to reduce flow-by. The zero flush seal operates at low pressures and allows more sprinkler heads on the same zone. The wiper seal's design protects the riser when operating and keeps debris out of the seal when retracted, reducing riser stick ups.



HEAVY-DUTY SPRING

The Pro-Spray line features the strongest retraction spring for positive retraction under any conditions.



PRO-SPRAY CHECK VALVE

Choose from the convenience of factory-installed or field-installed check valves to eliminate leaks and puddles at the lower heads, protecting landscapes from damage while reducing water waste.

PRESSURE-REGULATED TO 2.1 AND 2.8 BAR (210 AND 280 KPA)

Hunter's pressure-regulated, pop-up sprays are calibrated for the needs of any installation. The brown-capped PRS30 optimises performance of traditional sprays at 2.1 bar (210 kPa). The grey-capped PRS40 is designed for the efficient MP Rotator Nozzle and is the only 2.8 bar (280 kPa) regulated pop-up on the market today.



FLOGUARD™ TECHNOLOGY

In the event of a missing nozzle, FloGuard Technology reduces the flow of water from the riser to a 1.9 l/min (3 m tall) indicator stream, eliminating water waste and preventing landscape erosion while providing a visual indicator for repair.



NO-LEAK BODY CAP

Pedestrian traffic, landscaping equipment, temperature changes, and cycling pressures can cause body caps to loosen. Most spray bodies utilise an O-ring, which breaks the seal immediately after loosening. The Pro-Spray can withstand more than one full 360° turn and remain sealed at any pressure.



Competitor

Pro-Spray

PRO-SPRAY SPRINKLER BODIES

Pro-Spray

Designed for professionals, the Pro-Spray is the contractor's choice. Ready for commercial or residential projects, it's a rugged and reliable sprinkler for versatile applications.

Key Benefits

- Application: Residential/commercial
- Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm
- Innovative directional flush plug design
- Compatible with all female-threaded nozzles
- Side inlet (SI) version available in 15 cm and 30 cm models
- Optional factory- or field-installed check valve (up to 3 m of elevation)
- Warranty period: 5 years

Pro-Spray Reclaimed

Pro-Spray models come with optional factory-installed purple reclaimed caps.



Pro-Spray PRS with FloGuard Technology

Specify the FloGuard option on PRS models for added security against water waste and landscape erosion in the event of a missing nozzle.



BUILT-IN PRESSURE REGULATION REDUCES MISTING AND SAVES WATER

Pro-Spray PRS30

An in-stem 2.1 bar (210 kPa) regulator provides optimal pressure to reduce water waste.

PRS30 Features

- Models: Shrub, 7.5 cm, 10 cm, 15 cm, 30 cm
- Pressure-regulated at 2.1 bar (210 kPa)
- Side inlet (SI) version available in 15 cm and 30 cm models
- Identification cap is brown for easy field ID
- Optional factory- or field-installed check valve (up to 4.3 m of elevation)

Pro-Spray PRS40

Calibrated at a consistent 2.8 bar (280 kPa), the Pro-Spray PRS40 delivers optimal performance and water efficiency when combined with the revolutionary MP Rotator Nozzle.

PRS40 Features

- Models: Shrub, 7.5 cm, 10 cm, 15 cm, 30 cm
- Pressure-regulated at 2.8 bar (280 kPa)
- Side inlet (SI) version available in 15 cm and 30 cm models
- Identification cap is grey for easy field ID
- Optional factory- or field-installed check valve (up to 4.3 m of elevation)



Pro-Spray

Works Best With



Pro Fixed
Nozzles



Pro High-Efficiency
Nozzles



MP Rotator
Nozzles



Pro-Spray PRS30



Pro Fixed
Nozzles



Pro High-Efficiency
Nozzles



Pro-Spray PRS40



MP Rotator
Nozzles

Website hunterirrigation.com | **Customer Support** +1-760-752-6037

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.